

What is claimed is:

1. A method for detecting the presence of auxiliary information symbols encoded onto host signals, comprising steps of:
 - receiving an encoded host signal;
 - detecting an auxiliary information carrier from said received encoded host signal, wherein said auxiliary information carrier is comprised of a plurality of signal components having varying amount of delay or offset from each other;
 - correlating said encoded host signal with said auxiliary information carrier to obtain a correlation value; and
 - detecting the presence of said auxiliary information symbols from said correlation value.
2. The method according to claim 1, wherein said auxiliary information symbol detecting step comprises the step of determining the sign of said correlation value.
3. The method according to claim 1, wherein said auxiliary information symbol detecting step comprises the step of determining the magnitude of said correlation.
4. The method according to claim 1, wherein said auxiliary information symbol detecting step is used for copy management purposes.
5. The method according to claim 1, wherein said auxiliary information symbol detecting step is used to limit unauthorized copying of said host signal.
6. The method according to claim 1, wherein said auxiliary information symbol detecting step is used for at least one of broadcast and playback monitoring of said host signal.

7. A method for encoding information symbols onto a host signal, comprising the steps of:

creating an auxiliary information carrier, wherein said auxiliary information carrier is comprised of a plurality of signal components having varying amounts of delay or offset from each other;

determining a value of an auxiliary information signal representing an information symbol;

calculating a value of said auxiliary information carrier corresponding to said determined value of said auxiliary information signal according to a predefined relationship between auxiliary information signal value and auxiliary information carrier;

developing a host modifying signal for modifying said host signal based upon said calculated value; and

modifying said host signal with said host modifying signal.

8. The method according to claim 7, wherein said auxiliary information carrier comprises multiple distinct frequency bands.

9. The method according to claim 8, wherein said auxiliary information carrier comprises one or more frequency components within at least one of said frequency bands.

10. The method according to claim 7, wherein said calculated value comprises a fixed gain value of said auxiliary information carrier.

11. The method according to claim 10, wherein the polarity of said fixed gain value is determined in accordance with the value of said auxiliary information signal.
12. The method according to claim 7, wherein said information symbols identify said host signal.
13. The method according to claim 7, wherein said information symbols comprise copyright information associated with said host signal.
14. The method according to claim 7, wherein said information symbols identify an attribute of said host signal.
15. The method according to claim 14, wherein said attribute comprises copy management rules associated with said host signal.
16. The method according to claim 14, wherein said attribute comprises usage control rules associated with said host signal.
17. The method according to claim 14, wherein said attribute comprises distribution control rules associated with said host signal.
18. The method according to claim 7, wherein said host signal is stored on a physical medium subsequent to said encoding.
19. The method according to claim 7, wherein said host signal is distributed by least one of radio wave transmission and wired transmission subsequent to said embedding.